### DC125 Ladibug™

### Ultra-Portable High-Definition Visual Presenter




The Lumens™ DC125 high-definition document camera is operated with only one USB cable connected to a computer. This simple connection is enough to enable interactive presentations. The DC125 has a professional image sensor that delivers vivid colors at high-definition QXGA and Full HD 1080p output resolutions with 30 frames per second. Our jointless, highly flexible gooseneck enables a 360° viewing angle and object viewing from just 1.6″ (4 cm) to observe an object's finer detail. Press one button to get the perfect image quality every time. The DC125 Ladibug™ offers exclusive annotation over a live image for the best interaction, as well as one-touch video recording to record presentations saved in a variety of image formats on computer for playback. The stylish, lightweight design makes it easy to carry the DC125 anywhere quickly for creative presentations.

### **Key Features**

- Full HD 1080p Output Resolution
- Jointless, highly flexible gooseneck
- High Speed 30fps Dynamic Image
- Hands-Free Auto Focusing
- USB Cable Only
- Plug and Play
- Unique Image Optimization
- Special Water Droplet Design
- Compatible with All Major Brands of Interactive Whiteboards
- 5 Year Unlimited Replacement Warranty



#### **More Details**



### Excellent Image Quality

The DC125 is equipped with a professional image sensor that has high sensitivity when identifying brightness and contrast with low noise and vivid color reproduction. It supports high definition QXGA, Full HD 1080p, SXGA, and various signal formats for a crystal-clear image.

30 fps	< 24 fps

### Smooth Dynamic Image

The frame rate is as high as 30 fps, even at Full HD 1080p output resolution, which is much higher than the 24 fps of a movie theater. Higher frame rates capture every tiny movement without delays, and even flapping insect wings can be clearly observed in greater detail.



### User-Friendly Interface

All frequently used commands are integrated into buttons on the camera base for convenience like lamp on-off, image freeze, capture, and image optimization to adjust sharpness, brightness, and focus for the best image quality.



# USB Cable Only, Plug & Play

Only one USB cable is needed to connect to a computer for easy operation without an external power adapter or VGA cable to provide a clear desktop. This plug and play design avoids complicated installations and is compatible with all major IWB brands.



### **Hands Free AF**

The DC125 equipped with the most advanced intelligent image mechanism for continuous focus adjustments. The DC125 will adjust its focus automatically and quickly to ensure the best image quality without any distractions for presenters and audiences.



# Video/Audio Recording

The microphone with built-in video and audio recording makes the DC125 convenient for recording training sessions, meetings, seminars, lectures with annotation, and effective playback.



#### Jointless Gooseneck

The innovative, jointless, flexible gooseneck design ensures smooth movement without vibration. All details of an object can be viewed at any angle.



#### **Auto Tune**


There is a single button located on the base of the DC125. With one light touch, the DC125 will correct the color, focus, and brightness automatically to achieve perfect image quality every time.

### **Specifications**

Zoom Capacity	Mechanical Zoom : 8x, Digital Zoom : 8x
Output Resolution	XGA, SXGA, 720p, 1080p, UXGA, QXGA(2048x1536)
High Color Reproduction	ΔE*ab 8.58 (mean)
SNR	51 dB
Sharpness	MTF 1102 lines
Close-up	1.6"(4 cm)
Shooting Area	Max. 16.5" x 12.4" (420 x 315 mm) > A3
Frame Rate	30 fps
Lamp	Built-in LED on camera head
Power Supplied	USB Bus Power

USB Image Transmission	USB 2.0 (480 Mbps) high speed transmission
Video/Audio Recording	Yes, via software
Built-in Microphone	Yes
Image Capture	Single or Continuous Capture
Auto Tune	Yes, image optimization
Image Rotation	0°, 180°, Flip, Mirror
Anti-Theft	Kensington lock port
Free Lumens Software	Support PC Windows 8, 7, XP, Vista and Mac OSX; WIA and TWAIN interface
Optional Accessory	DC-A11 wireless module

#### **User Interface**







Lock Port

Lumens Integration, Inc. 4116 Clipper Court Fremont, CA. 94538 Phone: 888.542.3235 Fax: 510 252 1389 http://www.MyLumens.com Lumens Europe Stationstraat 5 1730 Asse, Belgium Phone: +32 (0) 2 452 76 00 Fax: +32 (0) 2 452 76 00 http://www.MyLumens.com