

# Triumph®

by IDEAL

## ➔ TRIUMPH 4850 EP

**AUTOMATIC PROGRAMMABLE CUTTER** · programmable "EP" back gauge control module with LED display stores 9 programs (up to 9 steps each) and frequently used measurements · control module features repeat cut and eject functions · electric blade, clamp, and back gauge drive · automatic clamp can be lowered or raised independently from blade · electronic hand wheel with variable speed control for manual back gauge setting · dual side guides on front and rear tables · optical cutting line · solid steel blade carrier · stand with storage shelf · **SAFETY FEATURES:** external blade depth adjustment · two-hand operation · transparent safety guards on front and rear tables · disc brake for instant blade stop · automatic blade return from any position · safety lock with key and main switch

Dimensions (D x W x H): 38 1/4 x 29 3/4 x 48 1/2 inches, Shipping weight: 556 lbs.




### "EP" CONTROL MODULE



The "EP" back gauge control module features a digital display and keypad for programming.

### OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

### ➔ TRIUMPH 4850 EP

Cutting width	18 7/8"
Cutting height	3"
Narrow cut	1 3/8"
Cutting length behind blade	17 1/4"
Table length in front of blade	13 3/4"
Motor	2 hp
Power supply	115 V, 60 Hz*

\* 20 amp dedicated line required

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
[www.mbmcorp.com](http://www.mbmcorp.com)

**IDEAL.MBM**  
CORPORATION

1 Regan Road, unit 12  
Brampton, Ontario L7A 1B8  
800-387-2528, fax: 905-840-1114  
[www.ideal-mbm.com](http://www.ideal-mbm.com)

All technical data is approximate and subject to change. © MBM Corporation, 10/2006.