

> 2604 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off in case of paper jam; automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times | wide, 10 ½" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on cutting shafts (strip- and cross-cut models) | 1 year warranty on super micro-cut cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy "twin drive system" with dust-proof gear box housing | high quality wooden cabinet mounted on casters | convenient shred bin | 26 gallon bin capacity (approximate)

Dimensions (D x W x H): $18 \frac{1}{2}$ x $22 \frac{1}{2}$ x $36 \frac{1}{2}$ inches, Shipping weight: 125 lbs.









CAPACITY INDICATOR



"ECC" (Electronic Capacity Control) indicator helps prevent paper jams by monitoring capacity levels during operation.

→ 2604 STRIP-CUT

Strip width 3/16"
Sheet capacity 27-30*
Security level 2

Feed opening 10 1/4"

Max. horsepower 1

→ 2604 CROSS-CUT

Particle size 3/16" x 1 ½"

Sheet capacity 20-22*

Security level 3 Feed opening 10 1/4"

Max. horsepower 1

→ 2604 CROSS-CUT

Particle size 3/32" x 5/8' Sheet capacity 12-14*

Security level 4

Feed opening 10 1/4"

Max. horsepower 1

→ 2604 SMC HIGH SECURITY

Particle size 1/32" x 3/16" Sheet capacity 7-10*

Security level 6

Feed opening 10 1/4"

Max. horsepower 1

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 1/2009. 103WNT.



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com Dealer: