

Panafax[®]
UF-5950



dependable

Plain Paper Laser Fax



- High-speed Super G3 Fax Transmission
- High-speed Scanning
- 480 Pages Large Document Memory
- Low Power Consumption



Panasonic ideas for life



A Reliable Fax with True Business Power

**Simple but Trustworthy
—True Business Power
is Here**

The Panafax UF-5950 inherits the real business power that has made the Panafax name synonymous with business faxes. Amazing, in spite of being small enough to fit easily on your desk, the UF-5950 comes loaded with all the features and functions you'd expect from a top-of-the-line business fax, not to mention Super G3 fax transmission. Even with high volume transmissions and reception, the UF-5950 easily handles any fax job. Offering true business-level performance, the UF-5950 is not only durable and highly reliable, it is also economical and practical.

Count on the Panafax UF-5950. The simplest solution to your business fax demands.

Business-Optimized Fax Capability

• High-speed Super G3 Fax Transmission

With Quick Memory Transmission, the UF-5950 dials as soon as the first page has been scanned even when sending a large, multi-page document.



• High-speed Scanning

Built for true business-level faxing, the UF-5950 scans documents quickly at a rate of 2.8*1 seconds per page. In combination with the 50-sheet automatic document feeder, this makes it possible for you to fax a multi-page document at the touch of a button without having to wait around.

• 480 Pages Large Document Memory

With its high-capacity 8 MB document memory, the UF-5950 can store up to 480 pages*2. This allows it to easily handle several high-volume jobs at once, so you'll never have to wait around.

Energy Saving

• Low Power Consumption

Thanks to our Energy Saver technology, the UF-5950's power consumption has been reduced to a mere 1.2 Wh in the sleep mode.

Panasonic®

Panasonic Digital Document Company
Unit of Panasonic Corporation of North America
One Panasonic Way, Secaucus, NJ 07094

► Features

- Auto Dialer One-touch: up to 32 stations
Abbreviated: up to 100 stations
Digit of Telephone number (up to 36 digits)
- Program keys (up to 4 Programs)
- Multi-Tasking Operation
- Directory Search Dialing
- Directory Sheet Print
- Intelligent Redial
- Chain Dialing
- Distinctive Ring Detector (DRD)
- Quick Memory Transmission
- Multi-station Transmission (up to 144 stations)
- Automatic Memory Retransmission
- Deferred Transmission
- Deferred Multi-station Transmission
- Priority Direct Transmission
- Edit File Mode with View Mode
- Automatic Cover Sheet
- Receive to Memory
- Substitute Reception
- Selective Reception
- Number of memory job files (Max. 10 files)
- Fax Forward
- Polling / Multi-station Polling (up to 144 stations)
- Deferred Polling/Deferred Multi-Station Polling
- Memory Polling Transmission (1 file)
- Confidential Mail Box*3 (10 mail boxes)
- Password Transmission/Reception*3
- ITU-T Sub-address Transmission
- Panasonic Super Smoothing (Fax/Copy)
- 64-Level Halftone
- Automatic/Fixed Reduction
- Overlapping Print
- Collation Stack
- Verification Stamp
- Communication Journal with image data
- Header/Total Page Print
- Transaction Journal with view mode
- Fax Access Code(Fax Lock)
- PIN Code Access
- Fax/Tel Auto Switch
- External TAM Interface
- Remote Reception
- Multi-Purpose LCD Display (20 x 2 lines)
- Multiple Copy with Sorting (up to 99 copies)
- Reduction Copy
- Energy Saver
- Remote Diagnostic
- Check & Call Function

► Options

- 250-sheet Universal Paper Feed Unit (UE-409070)
- Handset Kit (UE-403176)

► Consumable

- All-In-One Print Cartridge (toner/developer/drum) (UG-5515) 9,000-page Toner*4

► UF-5950 Specifications

Compatibility	ITU-T Group 3, ECM		
Modem Speed	33,600 - 2,400 bps with automatic fallback		
Coding Scheme	MH/MR/MMR		
Transmission Speed*5	Approx. 3 sec.		
Document Size	Max. 10.1" x 78.7" (257 mm x 2000 mm) (with operator's assistance) Min. 5.8" x 5.0" (148 mm x 128 mm)		
Effective Scanning Width	8.3" (212 mm)		
Automatic Document Feeder Capacity*6	50 sheets		
Document Thickness	Single sheet: 0.0024" - 0.0060" (0.06 - 0.15 mm) Multi-sheet: 0.0024" - 0.0039" (0.06 - 0.10 mm)		
Scanning Resolution (Fax)	Standard: 203 dots/inch x 98 lines/inch (8 dots/mm x 3.85 lines/mm) Fine: 203 dots/inch x 196 lines/inch (8 dots/mm x 7.7 lines/mm) Super Fine: 406 dots/inch x 391 lines/inch*7 (16 dots/mm x 15.4 lines/mm)		
Scanning Speed*1	Approx. 2.8 sec. (Letter, Standard mode)		
Recording Method	Laser printing on plain paper		
Printing Speed*8,9	6.5 ppm		
Recording Paper Size	Letter / Legal / A4, cut-sheet on plain paper		
Effective Recording Width	8.2" (208 mm) (Letter)		
Recording Paper Capacity	250 sheets (20 lb., 75 g/m2) With optional cassette: Approx. 500 sheets max. total		
Recording Resolution	Fax / Copy 406 dpi x 391 dpi		
Image Memory Capacity*2	8 MB (Approx. 480 pages)		
Power Requirements	AC 120 V, 60 Hz		
Power Consumption	Max. Approx. 470 W Sleep mode: 1.2 Wh		
Dimensions (W x D x H)*10	14.6" x 18.0" x 9.8" (370 mm x 457 mm x 250 mm) (Excluding projections and optional Paper Cassette)		
Weight*10	20 lb. (9.0 kg) (Excluding consumable supplies and optional equipment)		

*1 Scanning speed applies to the feeding process from the top to the end of a single page test chart.

The time for the feeding process does not include the time that it takes for the top edge of the page to reach the scanning point and page ejection. Time for entire storing process is not applied.

*2 Based on ITU-T Image No. 1 scanned in Standard mode.

*3 Panafax proprietary features work only with selected Panafax machines.

*4 Based on ITU-T Image No.1 scanned in multiple copy mode, set on fine resolution and using letter size recording paper. Yield may vary according to operating conditions and environment where the machine is installed.

*5 Transmission time applies to memory transmission of text data using only ITU-T Image No. 1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Usually public telephone lines can only support communications speeds of 28.8 Kbps or lower. Via PBX, transmission speed may fall back to a lower speed.

*6 Operating environment 20°C 50% Relative Humidity. Set the documents as stairs shape.

*7 Interpolated resolution (Optical Resolution: 203 dots/inch x 391 lines/inch)

*8 Speeds are contingent upon applications, machine configuration, and status. Individual speeds may vary.

*9 In multiple copy mode excluding the first copy.

*10 Dimensions and weights are approximate.

All other brand or product names are the property of their respective holders.

Design and specifications are subject to change without notice.

Panasonic proudly offers a 1 year exchange warranty on the UF-5950.



As an ENERGYSTAR® partner, Panasonic has determined that this product meets the ENERGYSTAR® guidelines for energy efficiency.

ISO 9001 Quality Management System

Our business processes which produce document, information and network products, from manufacturing to marketing, conform to ISO 9001 Quality Management Systems standard. Design, development, manufacture, installation, repair and maintenance of document, information and network products, their associated devices and consumables. In addition, the plants outside Japan have acquired ISO 9001 certification.

