



PLUS

Conceive your next idea here!

N-31 Series

Electronic Copyboards

Introducing industry leading features for saving, sharing and securing the notes from your meeting.



► Updated and added security. The next generation of copyboards.

The New N-31 series was specifically designed for offices or environments where protecting your information is top priority. Have confidence, knowing your information is secure.

Enhanced features:

- **Password Security and Validation** – Alpha numeric characters and special symbols can be used for password, instead of alpha only characters. Password validity time period can be adjusted.
- **SSL Security** – Data is transferred in encrypted format.
- **IC Card** – Intelligent Card, lets you initiate scan to FTP server.
- **Multiple Users** – Up to 100 users can be programmed into the board. Meeting notes can be saved to a specific users FTP site or to the boards' memory.
- **Multiple FTP Sites** – More than one FTP site can be accessed by the board.



The ideal environment for the N-31/314 series is where information is critically sensitive. This may include: Government agencies and subcontractors, OEM auto manufacturers' and suppliers, Architects, Engineers, Clothing industry, Footwear, Insurance Agencies, Financial Planning, Oil and Gas industry, Power & Electric, and others.

PLUS N-31 Series

Updated and added security. The next generation of PLUS Copyboards.

PLUS

Network Function

Connect to a network via an ethernet cable. There are two options for saving and sharing your information over the network.



• Save your copyboard data to the board's internal memory. Up to 100 users can be programmed into the board via 10-key pad. Using an assigned IP address, your team can access the images on the board from their computers using a web browser. The data on the board is accessible even in "Stand-by" mode. Administrator password can be added for greater board security.

• When connected to the network, you can save to multiple FTP sites so that everyone on your team has access to the saved information.

Access Via Your SmartPhone

Just install the Meeting Pocket App (MTGpocket) and gain access to many useful and time-saving meeting tools. Both Apple iOS® and Google Android™ mobile operating systems are supported, so you can use your iPhone®, iPad® or Android™ phone. The MTGpocket App lets you perform the "scan" function of the board from your SmartPhone. The resulting image file can then be previewed and saved to your phone's memory – as well as to the memory of phones belonging to anyone present in the meeting who has the MTGpocket App installed! Furthermore, the MTGpocket App lets you record audio and video during the meeting. The audio and video files are organized in the same folder as the board image files, so that all of the meeting data is in one convenient location. [Note: Using the MTGpocket App requires the connection of a "wireless access point" to the board as well as a compatible phone. Compatible with Apple iOS 4 and above and Android 2.3 and above.]



Built-in Software

There is no need to install software. Just connect your computer to the board via a USB cable whenever you want to save an image. Both PC and Mac compatible.

PDF, JPG and PNG Support

Users can easily save image files to USB memory or a PC in either PDF, JPG or PNG formats.

Smooth Hand-Scrolling

The surface of the N-31 Series boards are easy to move when using just your hand. The scrolling force needed has been reduced to 7 oz (0.2kg).

Faster Scanning Time

PLUS has once again improved scanning time. The N-31 boards (standard width models) scan in a mere 15 seconds.

Magnet Attachable

Magnets can be attached to the board surface.



Copyboards shown with optional printers and stands.

Specifications

	Model Name	Standard (N-31S)	Wide (N-31W)	4-screen (N-314)
Size	Installation Method	Wall Mount or Floor Stand ^{*1}		
	External Dimensions (Without Marker Tray)	W58.3 × D3.5 × H39.4 inches (W1480 × D89 × H1000 mm)	W78 × D3.5 × H39.4 inches (W1980 × D89 × H1000 mm)	W58.3 × D5.5 × H39.4 inches (W1480 × D140 × H1000 mm)
	Weight	44 lbs (20 kg)	55 lbs (25 kg)	55 lbs (25 kg)
	External Dimensions With Floor Stand (max.) ^{*1}	W58.3 × D26.6 × H76.6 ^{*2} inches (W1480 × D675 × H1947 ^{*2} mm)	W78 × D26.6 × H76.6 ^{*2} inches (W1980 × D675 × H1947 ^{*2} mm)	W58.3 × D26.6 × H76.6 ^{*2} inches (W1480 × D675 × H1947 ^{*2} mm)
	Floor Stand Weight	23 lbs (10.5 kg)		
Board	Panel Size	W51.2 × H35.8 inches (W1300mm × H910mm)	W70.9 × H35.8 inches (W1800mm × H910mm)	W51.2 × H35.8 inches (W1300mm × H910mm)
	Effective Reading Area	W50.4 × H35.4inches (W1280mm × H900mm)	W70.1 × H35.4inches (W1780mm × H900mm)	W50.4 × H35.4inches (W1280mm × H900mm)
	Number of Panels	2		4
	Grid	2 inch (50mm) Grid		
	Scrolling	Endless in one direction (Horizontal scrolling)		Bi-directional, endless (Horizontal scrolling)
	Drive Method	Motorized / Manual		
	Reading Method	CIS (Contact Image Sensor)		
	Reading Illumination Light Source	RGB LED		
	Reading Resolution	Main scanning direction (vertical sheet surface) 50 dpi (1.92 dots/mm) Sub scanning direction (horizontal sheet surface) 50 dpi (1.82 dots/mm)		
	Reading Time	Black & White: approx. 15 s Color: approx 15 s	Black & White: approx. 21 s Color: approx 21 s	Black & White: approx. 15 s Color: approx 15 s
Interface	USB Ports	3 Ports: Type B for PC and Type A for Printer and for USB Flash Memory		
	Saved Output	File Format	PDF, PNG & JPG	
	Resolution	2458 × 1728 dots (fixed)	3418 × 1728 dots (fixed)	2458 × 1728 dots (fixed)
	External Memory	Type	USB Flash Memory	
	Compatible FAT types	FAT 16, 32		
	Interface	USB2.0 ³		
	Network	LAN Port	RJ-45 (10Base-T/100Base-TX)	
		Supported Protocol	TCP/IP (FTP/FTPS, HTTP/HTTPS, DHCP, NetBIOS Name Service) ⁴	
	Printing	Printing Resolution	300 dpi or equivalent	
	No. Print Colors	Eight colors or two color monochrome		
Printer Interface	Conforming to USB 2.0 standards			
Add Functions	Clock	Used for the timestamp and for file dating properties (Includes backup battery for when there is a loss of power.)		
	PC Connection	Images can be acquired and device settings made via USB (using a browser)		
Power Supply	AC Power Adapter	Input: AC100-240V/50-60 Hz, Max 0.75 A Output: DC 12 V, 3.0 A		
	PC Consumption	In standby: 3W, During operation: 12W (not including printer)		
Usage Conditions	Temperature	10°C ~ 35°C		
	Humidity	30 ~ 85% (with no condensation)		
Operating Environment	OS	Windows XP (Home Edition/Professional Edition (Service Pack 2 or Later) / Vista (32 bit) / Windows 7 (32 bit / 64 bit) / Mac OS X® 10.5 or later		
	Web Browser	Windows: Internet Explorer 8.0 or greater Macintosh: Safari 5 or greater *Enable JavaScript		
Accessories		Markers (Black, Red, Blue, Green), Eraser, AC Power Adaptor, USB Cable (9 ft Length), User's Manual, Assembly Set-up Manual, Printer Shelf, Wall Mounting Brackets.		
Optional Accessories		Rolling Floor Stand (Part #423-084)		

¹1. Floor stand sold separately. The height is adjustable at 68.8, 72.7 and 76.6 inches (1747, 1847 and 1947 mm).

²2. The value indicated for "H" (height) is the maximum height.

³3. USB Memory device not included. The memory capacity corresponds to 32GB or Less.

⁴4. Printer sold separately. Check with your dealer for current available printer models.

*Please note that for quality improvement purposes, specifications and design are subject to change without prior notice.

Microsoft, Windows and Internet Explorer are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh, Mac, iPhone, iPad and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

PLUS Corporation of America

9610 SW Sunshine Ct., Suite 100
Beaverton, OR 97005
800-211-9001 · 503-748-8700
www.plus-america.com